

MOR-LIFE™

THE LATEST SCOOP IN SUPERIOR FINISHES!

Want improved performance for your quartz aggregate and pebble swimming pool interior finish? Look no further! Introducing Mor-Life™ the industry's ultimate additive that delays the setting of concrete and mortar mixtures! Just a few scoops of More-Life™ extends troweling time for superior results. It is compatible with all Portland-based pool finishes and provides years of proven service, making it the leading choice of swimming pool interior finish applicators worldwide.

Improve the look and strength of your interior finishes while making applications easier for you and your crew. Save time while you extend the life of your pools-and the satisfaction of your customers!

For information on Mor-Life™ and our other quality pool products, please call us today

800-333-2660

www.clindustries.com



MANUFACTURED BY C.L. INDUSTRIES

MOR-LIFE™



TRUST MOR-LIFE™ TO:

- Extend troweling time for a better exposed aggregate results.
- Mixes can use less water.
- Years of proven success.
- Excellent storage stability.
- Remains a free-flowing powder with no lumps.
- Compatible with all Portland based pool finishes.
- The leading choice of professional based swimming pool interior finish applicators.
- Specifically designed to improve performance of quartz aggregate and pebble swimming pool interior finishes.

POOL WALLS

AIR TEMPERATURE

POOL FLOORS

MIXING DIRECTIONS FOR PEBBLE APPLICATIONS (5) 95-LBS. PORTLAND CEMENT BAGS PER BATCH

3 TO 4 SCOOPS

70-80°F (21.1-26.6°C)

6 TO 8 SCOOPS

4 TO 5 SCOOPS

80-100°F (26.6-37.8°C)

8 TO 10 SCOOPS

6 TO 8 SCOOPS

ABOVE 100°F (37.8C)

12 SCOOPS MAXIMUM

MIXING DIRECTIONS FOR QUARTS FINISHES (13) 80-LBS. QUARTS BAGS PER BATCH

1 TO 2 SCOOPS

70-80°F (21.1-26.6°C)

3 TO 4 SCOOPS

2 TO 3 SCOOPS

80-100°F (26.6-37.8°C)

4 TO 5 SCOOPS

3 TO 4 SCOOPS

ABOVE 100°F (37.8C)

7 SCOOPS MAXIMUM



MANUFACTURED BY C.L. INDUSTRIES