

Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

| | |
|--|----------------------|
| IDENTITY/TRADE NAME (as used on Label and List): Sunstone "Pearl" | GENERIC NAME: |
|--|----------------------|

SECTION I : IDENTIFICATION

| | |
|---|--|
| MANUFACTURER'S NAME: C.L. Industries | EMERGENCY TELEPHONE NUMBER: 1-800-222-1222 |
| ADDRESS (NUMBER, STREET, CITY, STATE and ZIP CODE): 8188 S. Orange Ave. | TELEPHONE NUMBER FOR INFORMATION: 800-333-2660 |
| Orlando, FL 32809 | REVISION DATE: 8/15/2014 REPLACES: Nov-00 |
| | SIGNATURE OF PREPARER (optional) <i>C. Rodriguez</i> |

To Purchasers/Users: This MSDS contains important safety, health and environmental information. Federal regulations require that employers make this information available to their employees. If you are a reseller of this product, you should supply a copy of this MSDS to purchasers.

SECTION II : HAZARD(S) IDENTIFICATION

| | |
|---------------------------------|--|
| EMERGENCY OVERVIEW: | |
| POTENTIAL HEALTH EFFECTS | |
| ACUTE: | Dust can irritate the eyes and upper respiratory system. Slurry can dry the skin and cause alkali burns |
| CHRONIC: | Dust may cause inflammation of the tissue linings of the interior of the nose and cornea. Hypersensitive individuals may develop an allergic dermatitis. |
| EYES: | May cause irritation; dust may cause inflammation of the tissue linings of the eyes and cornea. |
| SKIN: | Secondary route of entry; May cause irritation. |

SECTION III : COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL DESCRIPTION

| COMMON NAME | C.A.S. NO. |
|--|------------|
| Portland Cement | |
| Rock (Raw Aggregates) | |
| Earth Minerals | |
| Various admix's in a proprietary blend | |

NOTE: Cement may contain very small quantities of hexavalent chromium and alkaline metal oxides, such as calcium oxide.

The components of this product are in compliance with the chemical notification requirements of TSCA. This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

SECTION IV : FIRST AID MEASURES

| | |
|-------------|--|
| EYES: | Irrigate eyes with continuously with gentle flowing lukewarm water or at specified eyewash stations for at least 15 minutes. Seek medical attention. |
| SKIN: | Wash exposed skin with soapy water. If rash or irritation occur, seek medical attention immediately. |
| INHALATION: | Remove from exposure into fresh air, seek medical attention. |

SECTION V : FIRE FIGHTING MEASURES

| | |
|-------------------------------------|---|
| FLAMMABLE PROPERTIES: | |
| Flash Point: not combustible | |
| Flammable Limits: not combustible | |
| LEL: | not applicable |
| UEL: | not applicable |
| SUITABLE EXTINGUISHING MEDIA | not combustible |
| UNUSUAL FIRE & EXPLOSION HAZARDS: | not combustible |
| SPECIAL FIRE FIGHTING INSTRUCTIONS: | This product will not burn and rock is not flammable. |

SECTION VI : ACCIDENTAL RELEASE MEASURES

SPILLS: Sweep up material; follow good housekeeping procedures. Wear personal protection equipment. Emergency procedures are not required.

SECTION VII : HANDLING AND STORAGE

Handling & Storage: In dusty environments use NIOSH approved respirator.

SECTION VIII : EXPOSURE CONTROL/PERSONEL PROTECTION

THRESHOLD LIMIT VALUE

RESPIRABLE DUST: 5 Milligrams per cubic meter

| | |
|---------------------------|--|
| TOTAL DUST: | 10 Milligrams per cubic meter |
| PARTICLES PER CUBIC FOOT: | 30 million |
| ENGINEERING CONTROLS: | Provide adequate ventilation. Local exhaust can be used, if necessary, to control airborne dust levels. |
| RESPIRATORY PROTECTION: | In dusty environments, the use of NIOSH approved respirators is recommended. |
| SKIN PROTECTION: | Barrier creams, gloves, boots and clothing to protect skin from prolonged contact. Have adequate ventilation. Wash yourself and your clothes thoroughly after use. |
| EYE PROTECTION: | Use OSHA certified goggles or glasses. |

SECTION IX : PHYSICAL AND CHEMICAL PROPERTIES

| | |
|------------------------|---|
| APPEARANCE: | Powder with sand, stone, tan, white or black raw aggregate. |
| COLOR: | Grey, white, or colored |
| VAPOR PRESSURE: | NA |
| VAPOR DENSITY (Air-1): | NA |
| SOLUBILITY IN WATER: | Slight |
| SPECIFIC GRAVITY: | NA |
| EVAPORATION RATE: | NA |
| BOILING POINT: | 4046 degree F |
| ODOR: | Odorless |

SECTION X : STABILITY AND REACTIVITY

| | |
|---------------------------|-----------------|
| CHEMICAL STABILITY: | Stable |
| INCOMPATIBILITY: | None |
| CONDITIONS TO AVOID: | None |
| HAZARDOUS DECOMPOSITION: | None |
| HAZARDOUS POLYMERIZATION: | Will not occur. |

SECTION XI : TOXICOLOGICAL INFORMATION

Not Available

SECTION XII : ECOLOGICAL INFORMATION

Not Available

SECTION XIII : DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of as common waste in compliance with federal, state and local regulations.

SECTION XIV : TRANSPORTATION INFORMATION

D.O.T.: Not restricted

IATA: Not restricted

SECTION XV : REGULATORY INFORMATION

Not Available

SECTION XVI : OTHER INFORMATION

None